

4RUNNER

Item		Area	U.S.A.			
Body Type			4Runner (2WD)	4Runner (4WD)		
Vehicle Grade			SR5V6	SR5	SR5V6	
Model Code			VZN120L-GKPGEA	RN130L-GKLSEA	VZN130L-GKMGEA	
Major Dimensions & Vehicle Weights	Overall	Length	mm (in.)	4490 (176.8)	←	←
		Width	mm (in.)	1690 (66.5)	←	1690 (66.5), 1715 (67.5)*1
		Height	mm (in.)	1680 (66.1)	←	1680 (66.1), 1710 (67.3)*1
	Wheel Base		mm (in.)	2625 (103.3)	←	←
	Tread	Front	mm (in.)	1430 (56.3)	←	1430 (56.3), 1475 (58.1)*1
		Rear	mm (in.)	1425 (56.1)	←	1425 (56.1), 1470 (57.9)*1
	Effective Head Room	Front	mm (in.)	984 (38.7), 963 (37.9)*2	←	←
		Rear	mm (in.)	—	—	—
	Effective Leg Room	Front	mm (in.)	1053 (41.5)	←	←
		Rear	mm (in.)	—	—	—
	Shoulder Room	Front	mm (in.)	1368 (53.9)	←	←
		Rear	mm (in.)	—	—	—
	Cargo Space	Length	mm (in.)	1773 (69.8)	←	←
		Width	mm (in.)	929 (36.6)	←	←
		Height	mm (in.)	914 (36.0)	←	←
	Overhang	Front	mm (in.)	755 (29.70)	←	←
		Rear	mm (in.)	1110 (43.7)	←	←
	Min. Running Ground Clearance		mm (in.)	230 (9.1)	←	230 (9.1), 260 (10.2)*1
	Angle of Approach		degrees	40°	←	40, 43*1
	Angle of Departure		degrees	23°	←	23, 25*1
Curb Weight	Front	kg (lb)	923 (2035)	941 (2075)	1050 (2315)	
	Rear	kg (lb)	782 (1725)	794 (1750)	812 (1790)	
	Total	kg (lb)	1705 (3760)	1735 (3825)	1862 (4105)	
Gross Vehicle Weight Rating	Front	kg (lb)	—	—	—	
	Rear	kg (lb)	—	—	—	
	Total	kg (lb)	2449 (5400)	←	←	
Fuel Tank Capacity	L (U.S. gal., Imp. gal.)		65 (17.2, 14.3)*6	←	65 (17.2, 14.3)*6, 71 (18.8, 15.6)*6	
Luggage Compartment Capacity	m ³ (cu. ft.)		—	—	—	
Performance	Max. Speed		km/h (mph)	155 (96)	150 (93)	165 (103)
	Max. Cruising Speed		km/h (mph)	125 (78)	120 (75)	130 (81)
	Max. Permissible Speed	1st Gear	km/h (mph)	55 (34)	37 (23)	36 (22)
		2nd Gear	km/h (mph)	101 (63)	69 (43)	68 (42)
		3rd Gear	km/h (mph)	155 (96)	105 (65)	107 (66)
		4th Gear	km/h (mph)	—	150 (93)	165 (103)
Turning Diameter (Outside Front)	Wall to Wall	m (ft.)	12.4 (40.7)	←	←	
	Curb to Curb	m (ft.)	11.4 (37.4)	←	←	
Engine	Engine Type		3VZ-E	22R-E	3VZ-E	
	Valve Mechanism		12-Valve, OHC	8-Valve, OHC	12-Valve, OHC	
	Bore x Stroke	mm (in.)	87.5 x 82.0 (3.44 x 3.23)	92 x 89 (3.62 x 3.50)	87.5 x 82.0 (3.44 x 3.23)	
	Displacement	cm ³ (cu. in.)	2959 (180.5)	2367 (144.4)	2959 (180.5)	
	Compression Ratio		9.0 : 1	9.3 : 1	9.0 : 1	
	Carburetor Type		MFI [EFI]	←	←	
	Research Octane No.	RON	91	←	←	
	Max. Output (SAE-NET)	kW/rpm (HP @ rpm)	112 / 4800 (150 @ 4800)	87 / 4800 (116 @ 4800)	112 / 4800 (150 @ 4800)	
Max. Torque (SAE-NET)	N·m/rpm (lb-ft @ rpm)	244 / 3400 (180 @ 3400)	190 / 2800 (140 @ 2800)	244 / 3400 (180 @ 3400)		
Engine Electrical	Battery Capacity (20HR)	Voltage & Amp. hr.	12 - 48, 12 - 52*3	←	12 - 48, 12 - 52*3	
	Generator [Alternator] Output	Watts	720	←	720	
	Starter Output	kW	1.4, 1.7*3	←	1.4	
Chassis	Clutch Type		—	Dry, Single Plate	Dry, Single Plate	
	Transmission Type		A340E	G58	R150F	
	Transmission Gear Ratio	In First		2.804	3.928	3.830
		In Second		1.531	2.142	2.062
		In Third		1.000	1.397	1.436
		In Fourth		0.705	1.000	1.000
		In Fifth		—	0.851	0.838
		In Reverse		2.393	4.743	4.200
	Transfer Gear Ratio H4/L4		—	1.000/2.566	1.000/2.566	
	Differential Gear Ratio (Front/Rear)		—/3.900	4.100/4.100	4.300/4.300, 4.556/4.556*1	
	Differential Gear Size (Front/Rear)	in.	—/8.0	7.5/8.0	←	
	Brake Type	Front		Ventilated Disc	←	←
		Rear		L.T. Drum	←	←
	Parking Brake Type			L.T. Drum	←	←
	Brake Booster Type and Size	in.		Tandem 8" + 9"	←	←
Proportioning Valve Type			LSP & BV	←	←	
Suspension Type	Front		Double Wishbone	←	←	
	Rear		4 Links	←	←	
Stabilizer Bar	Front		STD	←	←	
	Rear		STD	←	←	
Steering Gear Type			Recirculating Ball	←	←	
Steering Gear Ratio (Overall)			26.2 - 29.9, 19.0*4	←	19.0	
Power Steering Type			Integral Type	←	←	

*1 : With 10.5R15 Tire with 7JJ Wheel
 *2 : With Moon Roof
 *3 : Set Option with Cold Area Spec.

*4 : With Power Steering
 *5 : Set Option with 10.5R15 Tire
 *6 : The specified capacity includes unusable fuel volume which does not exceed 1/4 gallon.

